

Appl. No. 10/710,507  
Amdt. dated May 05, 2006  
Reply to Office action of March 10, 2006

### **Amendments to the Claims**

This listing of claims will replace all prior versions, and listings, of claims in the application.

### **Listing of Claims**

1. (Currently Amended) A method for testing an optical disc drive control PCB using a reference optical pick-up head, the method comprising:  
a step for determining a value by comparing an output of an optical disc drive control PCB under test to an output of a reference optical pick-up head laser; and  
5 a step for comparing the value to a pre-determined value and accordingly determining whether the optical disc drive control PCB under test is acceptable :  
a step for connecting the optical disc drive control PCB under test to the reference optical pick-up head; and  
a step for disconnecting the optical disc drive control PCB under test from the  
10 reference optical pick-up head when the test is complete.
2. (Original) The method of claim 1, further comprising a step for adjusting the output of the optical disc drive control PCB.
3. (Original) The method of claim 1, wherein the output of the reference optical pick-up head is from light emitted to a surface of an optical disc then reflected back to the  
15 optical pick-up head.
4. (Original) The method of claim 1, further comprising generating a pass/fail indication accordingly to the determination of acceptability of the optical disc drive control PCB under test.
5. (Original) The method of claim 1, further comprising generating a graphical  
20 characterization of the comparison of the measured value to the predetermined value.
6. (Canceled)
7. (Currently amended) The method of claim 6, wherein all steps are repeated for a

Appl. No. 10/710,507  
Amdt. dated May 05, 2006  
Reply to Office action of March 10, 2006

- batch of optical disc drive control PCBs under test.
8. (Original) A method for testing an optical disc drive control PCB using a reference optical pick-up head, the method comprising:
- 5 connecting the optical disc drive control PCB under test to the reference optical pick-up head;
- determining a value by comparing an output of an optical disc drive control PCB under test to an output of a reference optical pick-up head laser;
- comparing the value to a predetermined value and accordingly determining whether the optical disc drive control PCB under test is acceptable; and
- 10 disconnecting the optical disc drive control PCB under test from the reference optical pick-up head.
9. (Original) The method of claim 8, further comprising a step for adjusting the output of the optical disc drive control PCB.
10. (Original) The method of claim 8, wherein the output of the reference optical pick-up
- 15 head laser is measured using light emitted to a surface of an optical disc then reflected back to the reference optical pick-up head, or from light emitted by the laser directly via a polarizing beam splitter (PBS) of the reference optical pick-up head.
11. (Original) The method of claim 8, further comprising generating a pass/fail indication accordingly to the determination of acceptability of the optical disc drive control PCB
- 20 under test.
12. (Original) The method of claim 8, further comprising generating a graphical characterization of the comparison of the measured value to the predetermined value.
13. (Original) The method of claim 8, wherein all steps are repeated for a batch of optical disc drive control PCBs under test.
- 25 14. (Currently Amended) An optical disc drive control PCB test assembly comprising:
- a pick-up head for emitting and receiving laser light;
- means for laser power monitoring;
- means for presenting guiding instructions to assist in the adjustment of the optical disc

Appl. No. 10/710,507  
Amdt. dated May 05, 2006  
Reply to Office action of March 10, 2006

- drive control PCB under test; and  
means for electrically connecting an optical disc drive control PCB to the optical disc  
drive control PCB test assembly, wherein the optical disc drive control PCB test  
assembly may readily be used in the consecutive testing of a plurality of optical disc  
5 drive control PCBs.
15. (Original) The device of claim 14, wherein the test assembly further comprises a  
means of presenting a pass/fail indication.
16. (Original) The device of claim 14, wherein the test assembly further comprising a  
means of presenting guiding instructions to assist in the adjustment of the optical disc  
10 drive control PCB under test.
17. (Cancelled)